

STABLE, VERSATILE, AND EASY-TO-USE EQUIPMENT

Its high stability and highly secure features make this trailer-mounted platform an industry benchmark. This equipment is lightweight, versatile, and suitable for various types of work. It is quick to deploy and its hydra static drive allows it to move around and perform tasks quickly. Designed for easy operation and low maintenance, It is possible to deploy the platform on both sides of the trailer, but this requires prior configuration. This is the only type of equipment in our fleet that can also be rented for operation by the customer themselves.

HP35 SHORT CONFIGURATION	
	IMPERIAL / METRIC

PLATFORM RETRACTED LENGTH	18'10" / 5,5 M *
---------------------------	------------------

HP35 CONFIGURATION	
	IMPERIAL / METRIC

PLATFORM RETRACTED LENGTH	24'10" / 7,57 M
---------------------------	-----------------

* Can be inserted from a horizontal clearance of 2 meters

SPECIFICATIONS	
	IMPERIAL / METRIC

CAN REPLACE THE FOLLOWING EQUIPMENT	MBI 70, MBI 90, MBI 110, HPT38
-------------------------------------	--------------------------------

TOWER LENGTH	3'4" / 1,02 M
--------------	---------------

TOWER SEPARATION WIDTH	5'1" / 1.55 M
------------------------	---------------

TOWER ADJUSTMENT	±5 DEGREES
------------------	------------

MAXIMUM GUARDRAIL HEIGHT	5'9" / 1.75 M
--------------------------	---------------

MAXIMUM DISTANCE FROM THE GUARDRAIL	4'2" / 1,27 M
-------------------------------------	---------------

MAXIMUM GRADE	5 % (3 DEGREES)
---------------	-----------------

MAXIMUM SUPER ELEVATION	8 % (4,5 DEGREES)
-------------------------	-------------------

ROADWAY CLEARANCE	11'9" / 3,6 M
-------------------	---------------

OUTRIGGERS CLEARANCE	2'11" / 0,89 M
----------------------	----------------

WIDTH BETWEEN WHEELS	7'6" / 2,29 M
----------------------	---------------

HORIZONTAL CLEARANCE FOR TOWER ROTATION	1'4" / 0,42 M
---	---------------

VERTICAL CLEARANCE FOR TOWER ROTATION	2'10" / 0,86 M
---------------------------------------	----------------

VERTICAL ADJUSTMENT OF OUTRIGGERS	1'3" / 0,38 M
-----------------------------------	---------------

MAXIMUM DROP DEPTH	18'2" / 5.54 M
MAXIMUM PLATFORM SWING CLEARANCE	14'2" / 4,32 M
PLATFORM LENGTH	35' / 10.67 M
PLATFORM WIDTH - ALUMINUM SECTION	2'7" / 0.78 M
PLATFORM WIDTH - STEEL SECTION	3'1" / 0.94 M
PLATFORM WEIGHT CAPACITY	1 000 LBS / 455 KG
PLATFORM ROTATION	180 DEGREES
BIODEGRADABLE ECO-SYNTHETIC HYDRAULIC OIL	XL9525/046

TRAILER

OVERALL LENGTH	35' / 10,67 M *
OVERALL WIDTH	8'4" / 2,54 M *
OVERALL HEIGHT	10'6" / 3,2 M *
TOTAL WEIGHT (APPROXIMATE)	21 000 LBS / 9 525 KG *

* May vary depending on the truck chassis.